



	Honey Bee AirFlex	John Deere HydraFlex	Case TerraFlex	New Holland SuperFlex	Agco DynaFlex	Macdon FD75 FlexDraper
Vertical Flex Range	9"	7.5"	5.5"	5.5"	8"	10"
Operating Modes	Flex & Rigid (Adjustable from Cab)	Flex & Rigid (Partially Adjustable from Cab)	Flex & Rigid (Manual Adjust)	Flex & Rigid (Manual Adjust)	Flex & Rigid (Adjustable from Cab)	Flex & Rigid (Manual Adjust)
Cutter Bar	Independent	Attached to Frame	Independent	Independent	Independent	Attached to Frame
Float	Air System	Hydraulic	Torsion Spring	Torsion Spring	Hydraulic	Torsion Spring

## Center Deck

Draper Speed (fpm)	840	692	630	769	572	400
Center Deck Width	80"	60" – 68"	83"	83"	49"	79"

## Cutting System

Knife Drive	Mechanical Center Drive	Mechanical Side Drive	Mechanical Center Drive	Mechanical Center Drive	Mechanical Side Drive	Mechanical Side Drive
Knife Speed (spm)	1,280	1,040	1,260	1,260	1,200	1,400
Stroke Length	3"	4"	3"	3"	3.35"	3"

## Drapers

Drapers	Rubber V-guided	Rubber V-guided	Rubber V-guided	Rubber V-guided	Rubber V-guided	Rubber V-guided
Draper Speed (fpm)	760 (Fixed)	748 (Variable)	630 (Variable)	863 (Variable)	572 (Fixed)	464 (Variable)

## Reel

Reel & Fingers	Honey Bee Reel	HCC Reel	Custom Cam Reel	Custom Cam Reel	UII or HCC Reel	Macdon Cam Reel
Reel Drive	Center Driven Hydraulic	Center Driven Hydraulic	End Driven Hydraulic	End Driven Hydraulic	End Driven Hydraulic	Center Driven Hydraulic